



Self-Locking Nuts



GUK

Item NO.	Thread*pitch	H	h	D	D2	t	S	No.of Grooves for Hook	KG
		mm	mm	mm	mm	mm	mm		
GUK00	M10*0.75	7.4	4.5	18	15	15	3	4	0.009
GUK01	M12*1.0	7.4	4.5	21	18	18	3	4	0.009
GUK02	M15*1.0	8.4	5.5	24	21	21	4	4	0.012
GUK03	M17*1.0	8.4	5.5	28	24	24	4	4	0.018
GUK04	M20*1.0	9.4	6.5	32	27	27	4	4	0.025
GUK05	M25*1.5	10.3	6.5	38	33	33	5	4	0.035
GUK06	M30*1.5	10.9	6.5	44	38	38	5	4	0.046
GUK07	M35*1.5	11.1	7	50	44	44	5	4	0.062
GUK08	M40*1.5	12.1	8.2	56	50	50	6	4	0.080
GUK09	M45*1.5	12.1	8.2	62	55	55	6	4	0.095
GUK10	M50*1.5	12.7	8.5	68	61	61	6	4	0.130
GUK11	M55*2.0	13.2	8.5	75	68	68	7	6	0.160
GUK12	M60*2.0	13.2	8.5	80	73	73	7	6	0.170
GUK13	M65*2.0	14.3	9.5	85	77	77	7	6	0.185
GUK14	M70*2.0	14.3	9.5	92	84	84	8	6	0.230
GUK15	M75*2.0	15.3	10.5	98	89	89	8	6	0.270
GUK16	M80*2.0	16.3	11.5	105	96	96	8	8	0.340
GUK17	M85*2.0	17.3	12.5	110	100	100	8	8	0.390
GUK18	M90*2.0	17.5	12.5	120	110	110	10	8	0.540
GUK19	M95*2.0	18.5	13.5	125	115	115	10	8	0.600
GUK20	M100*2.0	19.5	14.5	130	120	120	10	8	0.680

*Unnecessary to add any tooth lock washer.

*Unnecessary to mill a keyway on the shaft and shorten its assembled time.

*Allow to be used after repeatedly screwing.

*Bearing any vibration and ensuring the integrated resistance when not tightened.

*The surface is galvanized to prevent rust.