


Material option:
 SAE1008 Low Carbon Steel
 C1045 Medium Carbon Steel
 SUS304 Stainless Steel



SUS301

Lock Nuts NO.	Thread(d*p)	D1	D2	A	C	B	h	H	Kg
AN00	M 10*0.75	18 0-0.2	13 +0.2	14(14.4)	0-0.2	2(1.8)	3 0.1	4 5.2	0.3 0.0070
AN01	M 12*1	22 0-0.2	17 +0.2	18(18.4)	0-0.2	2(1.8)	3 0.1	4 5.4	0.3 0.0075
AN02	M 15*1	25 0-0.5	21 0-0.5	21(21.4)	0-0.5	2(1.8)	4 0.2	5 6.5	0.5 0.0100
AN03	M 17*1	28 0-0.5	24 0-0.5	24(24.2)	0-0.5	2(1.9)	4 0.2	5 6.4	0.5 0.0140
AN04	M 20*1	32 0-0.5	26 0-0.5	28(28.4)	0-0.5	2(1.8)	4 0.2	6 7.7	0.5 0.0220
AN05	M 25*1.5	38 0-0.5	32 0-0.5	34	0-0.5	2	5 0.2	7 9.1	0.5 0.0350
AN06	M 30*1.5	45 0-0.5	38 0-0.5	41	0-0.5	2	5 0.2	7 9.1	0.8 0.0480
AN07	M35*1.5	52 0-0.5	44 0-0.5	48	0-0.5	2	5 0.2	8 10.2	0.8 0.0750
AN08	M 40*1.5	58 0-0.5	50 0-0.5	53	0-0.5	2.5	6 0.2	9 11.2	0.8 0.0980
AN09	M 45*1.5	65 0-0.5	56 0-0.5	60	0-0.5	2.5	6 0.2	10 12.5	1.0 0.1400
AN10	M 50*1.5	70 0-0.5	61 0-0.5	65	0-0.5	2.5	6 0.2	11 13.5	1.0 0.1670
AN11	M 55*2	75 0-0.5	67 0-0.5	69	0-0.5	3	7 0.2	11 13.5	1.0 0.1700
AN12	M 60*2	80 0-0.5	73 0-0.5	74	0-0.5	3	7 0.2	11 13.5	1.0 0.1950
AN13	M 65*2	85 0-0.5	79 0-0.5	79	0-0.5	3	7 0.2	12 15.0	1.5 0.2240
AN14	M 70*2	92 0-0.5	85 0-0.5	85	0-0.5	3.5	8 0.2	12 15.0	1.5 0.2920
AN15	M 75*2	98 0-0.5	90 0-0.5	91	0-0.5	3.5	8 0.2	13 15.8	1.5 0.3300
AN16	M 80*2	105 0-0.5	95 0-0.5	98	0-0.5	3.5	8 0.2	15 18.6	1.5 0.4200
AN17	M 85*2	110 0-0.5	102 0-0.75	103	0-0.5	3.5	8 0.2	16 19.2	1.5 0.5050
AN18	M 90*2	120 0-0.5	108 0-0.75	112	0-0.5	4	10 0.3	16 20.3	1.5 0.6900
AN19	M 95*2	125 0-0.5	113 0-0.75	117	0-0.5	4	10 0.3	17 21.3	1.5 0.7550
AN20	M 100*2	130 0-0.5	120 0-0.75	122	0-0.5	4	10 0.3	18 22.3	1.5 0.8550

Dismiss the traditional manufacturing method

Prolong the life cycle of machinery

Increase the manufacturing efficiency

Raise the machinery safety