



●配合軸端：一般用（高負荷） ●芯承受軸向負荷時用配合
 φ7：一般用（輕負荷） SPW組合使用、
 φ7：高轉速用

Length									Tolerance ^{-0.1} _{-0.3}		ID	OD	Mating washer SPW
50	60	70	80	100	120	130	140	150					
SPB	SPB	SPB	SPB	SPB	SPB	SPB	SPB	SPB					
										8	12	-----	
										10	14	-1003	
										12	18	-1203	
										13	19	-1303	
										14	20	-1403	
										15	21	-1503	
										16	22	-1603	
										18	24	-1803	
-202850										20	28	-2005	
										20	30	"	
-253350	-253360									25	33	-2505	
-253550										25	35	"	
-303850	-303860									30	38	-3005	
-304050	-304060									30	40	"	
										31.5	40	-----	
-354450	-354460									35	44	-3505	
-354550	-354560									35	45	"	
-405050	-405060	-405070	-405080							40	50	-4007	
-405550	-405560									40	55	"	
-455550	-455560									45	55	-4507	
-455650	-455660									45	56	"	
-456050	-456060	-456070	-456080							45	60	"	
-506050	-506060	-506070	-506080							50	60	-5008	
-506250	-506260	-506270								50	62	"	
-506550	-506560	-506570	-506580	-5065100						50	65	"	
-557050	-557060	-557070								55	70	-5508	
-607450	-607460	-607470	-607480							60	74	-6008	
-607550	-607560	-607570	-607580	-6075100						60	75	"	
	-637560	-637570	-637580							63	75	-----	
-658050	-658060	-658070	-658080							65	80	-6508	
-708550	-708560	-708570	-708580	-7085100						70	85	-7010	
-709050	-709060	-709070	-709080							70	90	"	
-759050	-759060	-759070	-759080	-7590100						75	90	-7510	
	-759560	-759570	-759580	-7595100						75	95	"	
-809650	-809660	-809670	-809680	-8096100	-8096120					80	96	-8010	
-8010050	-8010060	-8010070	-8010080	-80100100	-80100120			-80100140		80	100	"	
-9011050	-9011060		-9011080	-90110100	-90110120					90	110	-9010	
-10012050	-10012060	-10012070	-10012080	-100120100	-100120120			-100120140		100	120	-10010	
-11013050		-11013070	-11013080	-110130100	-110130120					110	130	-----	
		-12014070	-12014080	-120140100	-120140120			-120140140		120	140	-12010	
				-125140100	-125145120					125	145	-----	
			-13015080	-130150100		-130150130				130	150	-----	
				-140160100				-140160140		140	160	-----	
			-15017080	-150170100					-150170150	150	170	-----	
			-16018080	-160180100					-160180150	160	180	-----	